

(

PIMPRI CHINCHWAD MUNICIPAL CORPORATION JAGADGURU SANT TUKARAM MAHARAJ SANTPITH SCHOOL & JR. COLLEGE



Patilnagar, Talgaon Chikhali, Pune - 411062

Affiliation No: 1120131

School Code: 32147

UDISE CODE: 27252000538

Contact No: 9022816058

E-mail: santpithschool@gmail.com

जा.क्र.संतपीठ/स्कूल/०१/कावि/ 69 /२०२५-२६

दिनांक - ७ /०७/२०२५

विषय: पिंपरी चिंचवड महानगरपालिका संचलित जगदगुरु संत तुकाराम महाराज संतपीठ स्कूल ॲन्ड ज्युनिअर कॉलेजमध्ये सॅनेटरी नॅपकीन व्हेडिंग मशीन आणि सॅनेटरी वेस्ट इन्सिनरेटर खरेदी करणेबाबत...

कोटेशन नोटीस क्र. ०४/२०२५ - २०२६

पिंपरी चिंचवड महानगरपालिका संचलित जगदगुरु संत तुकाराम महाराज संतपीठ स्कूल ॲन्ड ज्युनिअर कॉलेजमधील महिला कर्मचारी व विद्यार्थिनींच्या आरोग्याच्या दृष्टीने आवश्यक असणारे सॅनेटरी नॅपकीन व्हेडिंग मशीन आणि सॅनेटरी वेस्ट इन्सिनरेटर खरेदी करणेकामी सीलबंद दरपत्रके मागविण्यात येत आहे. त्याचा तपशील पुढीलप्रमाणे...

	साहित्याचा	2007	नग	सर्व करांसह
अ.क्र	तपशील	स्पेसिफिकेशन	संख्या	प्रति नग दर
१.	सॅनेटरी नॅपकीन	सॅनेटरी नॅपकीन व्हेडिंग मशीन	. १	
	व्हेडिंग मशीन	GENERAL –		
	-010111111	1. Type of machine - Automatic.	1	· ·
		2. Type of fitting - Wall Mountable		
		3. Napkin Size for loading - Regular	1	
		4. Napkin Fold - Without fold		
		5. Multiple coins accepted – optional		
		6. Number of Napkins/pads provided/loaded with the vending	. ,	
		machine - 50		
		7. Multiselection of Napkin type - Yes	1	
		8. Number of selection options - 1	1	
		9. Vending option – Horizontal.		
		10. Accessibility for free vending utility service - should be available		
		11. Vending Napkin individually packed - Yes		
		12. LED illumination provided for visibility of Napkins in the	1	
		machine – Yes	2 -	
		13. Pre-programmable facility available - Yes	<u> </u>	
		14. Maximum Storage Capacity (Nos)(Nos) - 50-75		
		15. Digital counter for accounting - Yes16. "No stock" message display available - Yes.		
		16. "No stock" message display available 17cs. 17. Built-in program for automatic coin return/reject system when		
		there is no stock or no power- yes.		
		18. Built-in program for automatic currency block/reject system when		
		there is no stock or no power - Yes.	1	1.0
			1 - 1	
		– Yes		
		FUNCTIONAL FEATURES		
		1 1 1 (1) (0)	1 1	
			1 1 1 7	
		11 70 1		
		4. All MS parts are duly painted by - Powder coating5. Mode of function - Stand-alone.		
		6. Operating Power source – Electronic		
		7. Input Power supply - 220v +/- 10%, 50Hz, Single Phase AC.	1	
		8. Battery Backup available - Yes		
	= 1	9. Battery Backup time (hrs.) - 20-24		
		y. Buttery Buckup time (ms.) 20 24	1	
		DEMENSION		
		1. Width (mm) - 200-400		
	,	2. Depth (mm) - 100-200	1	
		3. Height (mm) -500-800	d , d	
ĺ		4. Weight (kg) - 21-30		
ı		5. Thickness of SS/MS sheet (mm) - 1.2		1

		. 1			
		1	CERTIFICATION OF THE CERTIFICA	3 / 1	
			6. Thickness of FRP/Plastic sheet (mm) - 1-2		
		1 P	PACKING		4
			1. Type of Packing - Cartoon Box		N -278 _ 1
			CERTIFICATIONS		
			1. Submission of Test Report on form 39 or form Central		
			Govt/NABL/ILAC accredited Lab or Manufacture's in house Test Report to prove the conformity to declared		
		-	specification at the time of supply - Yes	1111	
		7.	2. Certification Available - EU-CE		
		1	3. Certification for Manufacturing Premises - ISO 9001 2015	3 1.3	9
			4. Submission of all the certifications to the buyer along with	4 1 2	
			supplies - Yes	1 1 1 1	
	٦.	सॅनेटरी वेस्ट	सॅनेटरी वेस्ट इन्सिनरेटर	8	
	٧.		GENERAL :		H
		इन्सिनरेटर	1. Type - Wall Mountable		
			2. Purpose - Burn used Sanitary Napkins to sterile ash and stop	1.	
			automatically.	111	2.5
			3. Operation Mode -Electronically operated, fully automatic.		
			4. Loading Type- Front loading	1111	
			5. Stand provided — Yes 6. Number of chambers - Two		
			7. Trap Door available – Yes	1 1	
			8. All MS parts Powder coated – Yes	8 - 4	
			9. Spare parts should be available for Minimum 5 years from date of		
			supply- Yes		
			10.All electrical parts are ISI Marked – Yes		
				. P 1-2	
			DIMENSIONS OF MAIN UNIT 1. Thickness of thermal Insulation material (mm) - 40 millimeter.	+	
			2. Thickness of MS/SS sheet of housing cabinet (external) (mm) - 1.2		
		•	millimeter	1	9 4
			3. Thickness of MS/SS sheet of burning chamber (internal) (mm) (Min)		
		•	- 5 millimeter		. 1 12 7
			4. Machine Depth (mm) 301-500	111	
			5. Machine High (mm) 501-700	3 1 14	
			6. Machine Weight(kg) 31-50	313	
			7. Door width(mm) 101-150 8. Door height(mm) 50-100	4 1	
			9. Thickness of door including insulation(mm) 40 millimeter		
	31.50	1911	10. Flexible emission Outlet piped a (mm) - 50 millimeter		
・			11. Detachable ash tray – YES		
	100				
		and the second	MATERIAL OF MACHINE UNIT	17.	
			1. Material of Housing cabinet (External) - Mild Steel (CRCA) sheet 2. Material of Burning chamber (Internal) -Mild Steel(CRCA) sheet		
		×4	3. Finish of MS parts of cabinet - Epoxy anti rustproof painting for	1	
		a,	superior finish	\$. 7.	
		1.	4. Material of Thermal Insulation - High Density Ceramic Board		,
				4 21	1. 1.31
		. 3	CONSTRUCTIONAL FEATURES	\$ Y.	
		90 t	1. Thermal insulation of burning chamber housed in outer_chamber –		
		- 4	Yes 2. Burning Chamber tray provided-Yes	. 1	,
		\$-	3. Emission Outlet pipe location -Top of machine	1	
			4. Means of connecting the unit outlet with flue gas emission pipe-		
		81.7	Clamped		
		The second	5. Type of door lock provided- Magnetic lock	3 137	
		100			
			CONTROL & FUNCTIONAL FEATURES	4	
		- 1	1. Temperature indicator provided - Yes		
			2. Timer provided – Yes3. Auto cut-off temperature display – Yes	, ,	
			4. Digital display to see actual and set temperature- Yes	. / %	-
		in a second	5. Minimum Burning temperature (degree C)- 800	* *	
		* W	6. Burning Capacity per day (Number of Napkins) - 100-200		
			7. Burning time of full capacity Napkins/pads (minutes) (Max) - 15	ji i	
			minute 9. Skin temperature of the unit and the control of the con	1. 1.	
			8. Skin temperature of the unit under operation (deg C) - 0-159. Installation, training, demonstration and plumbing included Yes		141
			,		10 mg/m²

(

(

(

Ţ

ELECTRICAL AND SAFETY FEATURES

- 1. Automatic digital controller for time Yes
- 2. Automatic digital controller for temperature Yes
- 3. Equipment ON/OFF indicator provided Yes
- 4. Power supply- 230v +/-10%, 50Hz, Single-phase, AC supply
- 5. Electrical Power Consumption (Watt) 1501- 3000
- Minimum length of power chord to be supplied along with machine (mtr) - 2 meter
- 7. Power saver (auto power cut-off) Yes
- 8. Safety MCB provided (16A to 30A) Yes
- 9. Protection against electric shock when checked as per IS:302-
- 10. Minimum Insulation Resistance (IR) at 500VDC (Mega Ohm) 2
- 11. Maximum Electrical Insulation and Leakage current as per IS:302-1/2008, (mA)-0.21
- 12. Maximum Earthing continuity test when tested as per IS:302-1/2008 (Ohm) 0.1
- 13.HV test at 1000 V rms for 1 Sec when tested asper IS:302-1/2008
 No breakdown shall occur during the test

SMOKE CONTROL UNIT (SCU)

- 1. Type of SCU (Smoke Control Unit) Side Mounted
- 2. Material of housing of Smoke Control Unit (SCU) Mild Steel(CRCA) cabinet
- 3. Finish of MS parts of SCU cabinet Epoxyanti rust proof painting for superior finish
- 4. Overall height of SCU (mm) 300
- 5. Overall width of SCU (mm) 301-500
- 6. Overall depth of SCU (mm) 301-500
- 7. Number of chambers for filtration of smokeemission Two
- 8. Both carbon Control and Foul odour Control Chambers for filteration of smoke emission Yes
- 9. Number of filters in Carbon controlChamber -Two
- 10. Type of filters in Carbon control chamber -Teflon filter, Activated Carbonfilter & Steel mesh filter
- 11. Number of filters in Odour controlchambe Two
- 12. Type of filters in Odour control chamber- Activated Carbon filter
- 13. Blower type -"Centrifugal, direct driven"
- 14. Power supply of SCU 230v +/-10%,50Hz, Single phase, AC supply
- 15. Minimum length of flexible emission outlet pipe to be supplied along with machine (mtr) 3
- 16. Cost of additional flexible emission outlet pipe, if required on actuals to be paid by the user NO

EMISSION STANDARD FOR SMOKE

 Conformity to CPCB, Min of Environment & Forests standard, Solid Waste Management Rules (SWM), 2016 - Yes

MARKING AND INSTRUCTIONS

1. The appliance is marked as perIS:302-1/2008 - Yes

CERTIFICATION

- Submission of Test Report from Central Govt/CSIR
 Lab/NABL/ILAC accredited Lab specifically containing Electrical
 & Electronic parameters, Thermal insulation material of burning chamber in addition to declared specification parameter at time of supply Yes
- Submission Test Report for equipment for compliance of Flue gas emission and ash upon combustion of Sanitary Napkins/Pads to Central Pollution Control Board (CPCB) norms from NABL accredited lab/CSIR Lab at the time of supply - Yes
- 3. Certification Available EU-CE
- 4. Certificate for Manufacturing premises available- ISO
- 5. Compliance certificate is to be furnished after conducting comprehensive performance test by the supplier Yes

कोटेशन नोटीस व नियम अटी खालीलप्रमाणे आहेत.

१. इच्छुक ठेकेदारांनी / पुरवठाधाराकांनी उपरोक्त नमूद केलेल्या साहित्य / कामाचे दर दिलेल्या स्पेशिफिकेशन नुसार व आवश्यक त्या कागदपत्रांसह सिलबंद पाकिटात मा.प्राचार्य, जगदगुरू संत तुकाराम महाराज संतपीठ स्कूल ॲन्ड ज्युनिअर कॉलेज, पाटीलनगर, टाळगाव चिखली यांचे नावे दिनांक ०१/०८/२०२५ ते ०८/०८/२०२५ अखेर दुपारी ३:०० वाजेपर्यंत जगदगुरू संत तुकाराम महाराज संतपीठ स्कूल ॲन्ड ज्युनिअर कॉलेज, पाटीलनगर, टाळगाव चिखली, तालुका - हवेली, जिल्हा - पुणे ४११०६२ येथे सादर करावे.

- २. पुरवठा धारकाने कोटेशन सोबत शॉप ॲक्ट नोंदणी दाखला, पॅनकार्ड, आयकर भरत असलेबाबतचा मागील २ वर्षाचा पुरावा इ. कागदपत्रांच्या प्रती सादर करण्यात याव्यात.
- ३. पुरवठा धारकाने आपले दर सर्व करासह व वाहतूक खर्चासह पोहोच देण्यात यावे.
- ४. कोटेशन नोटीसमधील नमूद स्पेसिफिकेशनुसार सॅनेटरी नॅपकीन व्हेडिंग मशीन आणि सॅनेटरी वेस्ट इन्सिनरेटर साहित्याचा पुरवठा स्वखर्चाने जगदगुरू संत तुकाराम महाराज संतपीठ स्कूल ॲन्ड ज्युनिअर कॉलेज हे पाटीलनगर, टाळगाव चिखली येथे करावा लागेल. तसेच सदर साहित्य सदर शाळेतील अधिकारी यांचे सुचणे नुसार स्थापित करावे लागेल.
- पुरवठा आदेशानुसार दिलेल्या मुदतीत सदर साहित्याचा पुरवठा न केलेस प्रतिदिनी रक्कम रुपये ५००/- विलंब शुल्क आकारणेत येवून त्याची देय बीलातून वसुली करणेत येईल.
- ६. मंजूर केलेले दर सदर साहित्याचा पुरवठा पूर्ण होईपर्यंत पुरवठाधरकावर बंधनकारक राहतील.
- ७. पुरवठा धारकास कोणत्याही प्रकारची भाववाढ / नुकसान भरपाई मिळणार नाही.
- ८. सिलबंद कोटेशन पाकिटावर नोटीस क्रमांक फर्म /कंपनीचे नावाचा स्पष्ट उल्लेख करावा.
- ९. उशिरा आलेल्या व अपुऱ्या तसेच अटीयुक्त कोटेशनचा विचार केला जाणार नाही.
- १०. कोटेशन संपूर्ण प्रक्रियेबाबत कोणताही वाद निर्माण झाल्यास मा. सचिव (जगदगुरू संत तुकाराम महाराज संतपीठ) हे लवाद म्हणुन जो निर्णय देतील तो अंतिम राहील. जो उभयंतावर बंधनकारक राहील.
- ११. सदरचे काम हे मा. सचिव / प्राचार्य यांच्या सूचनेनुसार करावयाचे आहे. त्यांच्या पोहोच चलनानुसार बील अदा करणेत येईल.
- १२. कोणतेही कोटेशन मंजूर अथवा नामंजूर करण्याचा अधिकार मा. सचिव, जगदगुरू संत तुकाराम महाराज संतपीठ यांनी राखून ठेवला आहे.
- १३. सदरची कोटेशन नोटीस संतपीठाचे www.santpithpcmc.com या अधिकृत वेबसाईटवर प्रसिद्ध करणेत आलेली आहे.

Plakler

संगीता बांगर (घोडेकर)

सचिव

जगदगुरु संत तुकाराम महाराज संतपीठ